

WWW.SESHREDDERS.COM

OUR PRODUCTS

PAR 60110



SE OFFERS A VARIETY OF SHREDDING SOLUTIONS TO PROCESS SCRAP TIRES FOR CARS, TRUCKS, CONVEYOR BELTS ETC.



This powerful dual-shaft shredder easily handles whole passenger and light truck tires with output shreds down to 25-75 mm chips.



PAR 60110 can shred tires and various scrap rubber products at rates from 2-3 tons / hour (200-300 car tires).



THE DUAL-SHEAR ADVANTAGE


- High-torque shearing technology efficiently processes tough materials.
- Wear-resistant cutters
- Shock protection
- Bulk feed capability
- Low noise, dust, heat generation and maintenance costs
- Energy efficient operation
- Heavy-duty construction
- Minimum foundation requirements



PAR 60110

DUAL - SHEAR

Drive	Hydraulic
Number of Motors	One (HPU)
Power Range	110 Kw
Voltage	460/3/60
Voltage Options	Many - Consult Factory
Autochop Feature	Included
Shock Load Protection	Yes (Multiple Relief)
Cutter Thickness (nominal)	25 mm
Cutter Diameter	390 mm
Shaft Diameter	152 mm
Cutting Chamber (WxL)*	710 x 1200 mm
Machine Length *	2935 mm
Machine Width	790 mm
Machine Height	1980 mm
Machine Weight	3700 kg
Hopper Opening *	1000 x 1500 mm
Hopper Height	750 mm
Stand Height	1000 mm
Hidrolic Power Unit	Closed loop
Cutterset	2 Types cutterset
Manufactured for	RDF, Metal and Tire Shredding
Working Pressure	Up to 250 bar (Back opening protection system)
Hydrolic Pumps	A4V 125 (used as TANDEM); produce 1500 rev and 190 liter oil
Hydromotor Type	SAUER 23 (double) 89 liter
Revoliyion of Rotor	80-120 rev/min
Gears	QK 9 (Excavator walking groups -double- EL20QEH2EOW)
Capacity	2000-3000 kg/hr (for each shredder)



SE SHREDDERS

A : 4.Cadde No:12 Gerede
OSB Bolu , TURKEY
14900

M : info@seshredders.com
T : +90 374 333 00 56

WWW.SESHREDDERS.COM